


Features

- ◆ Low Cost
- ◆ Low Power Consumption
- ◆ Low Phase Noise
- ◆ Fast Settling Time
- ◆ Integrated VCO, PLL IC, Loop Filter

Applications

- ◆ Commercial Wireless Applications



Electrical Specifications, $T_A = +25^\circ\text{C}$, $V_{CC} = +5\text{V}$ (unless otherwise stated)

Parameter	Units	Min	Typ	Max
Frequency Range –	MHz	851		877
Step Size	kHz		200	
Settling Time – To within 1 kHz	mSec		5	10
Output Power –	dBm	1.0		3.0
Output Phase Noise:				
1 kHz	dBc/Hz		-80	-78
10 kHz	dBc/Hz		-109	-105
100 kHz	dBc/Hz		-130	-126
Power Supply –	Volts	3.20	3.30	3.40
Supply Current	mA		24	28
Spurious Product – 200 kHz	dBc		-80	-75
Reference Feedthrough –	dBc		-80	-75
Harmonic Suppression:				
2nd Harmonic	dBc		-13	-10
3rd Harmonic	dBc		-20	-10
Ref Osc Signal				
Frequency	MHz		12.8	
Amplitude	dBm		-2.0	
Phase Noise – 1 kHz	dBc/Hz		-145	
Input Impedance	k Ω		100	
Output Impedance –	Ω		50	
Operating Temperature Range	$^\circ\text{C}$	-40		+85

Comments

All specifications apply with a 50 ohm load impedance.