



SURFACE MOUNT MODEL VOLTAGE CONTROLLED OSCILLATOR

Frequency 890-1100MHz

VL1100M

FEATURES:

- ▶ Miniature Size
- ▶ Surface Mount Package
- ▶ Low Phase Noise Performance
- ▶ Electrically Shielded
- ▶ Highly Linear Tuning



Electrical Specifications, $T_A = +25^\circ\text{C}$, $V_{CC} = +5.0\text{V}$ (unless otherwise stated)

Parameter	Test Conditions	Min	Typ	Max	Units
Frequency Rangs		890		1100	MHz
Tuning Voltage (V)		1.0		13.0	V
RF Output Power	890-1100MHz	4.0		8.0	dBm
Supply Voltage (Vcc)		4.75		5.25	V
Supply Current (Icc)			17	20	mA
Phase Noise :					
	@10kHz Offset:		-110	-107	dBc/Hz
	@100kHz Offset:		-131	-128	dBc/Hz
Average Tuning Sensitivity	890-1100MHz		25		MHz/V
Harmonic Outputs			-6.0		dBc
OperatingTemperature Range		-55		+85	$^\circ\text{C}$
Tune Input Capacitance			36		PF
Output Impedance -			50		Ω
Package Type	SK605(12.7X12.7X4.3mm)				



SMD Voltage Controlled Oscillator

Frequency 889-1100MHz

VL1100M

[illegible]