




SURFACE MOUNT MODEL VOLTAGE CONTROLLED OSCILLATOR

Frequency 1250-1732MHz

VL1732F

FEATURES:

- ▶ Miniature Size
- ▶ Surface Mount Package
- ▶ Low Phase Noise Performance
- ▶ Electrically Shielded
- ▶ Highly Linear Tuning



Electrical Specifications, $T_A = +25^{\circ}\text{C}$, $V_{CC} = +5.0\text{V}$ (unless otherwise stated)

Parameter	Test Conditions	Min	Typ	Max	Units
Frequency Rangs		1250		1732	MHz
Tuning Voltage :					
	VT1:	1.6		2.6	V
	VT2:	-0.5		-11.0	V
RF Output Power	1250-1732MHz	5.0		9.0	dBm
Supply Voltage (Vcc)		4.75		5.25	V
Supply Current (Icc)			20	23	mA
Phase Noise :					
	@10kHz Offset:		-106	-103	dBc/Hz
	@100kHz Offset:		-126	-123	dBc/Hz
Average Tuning Sensitivity	1250-1732MHz		50		MHz/V
Harmonic Outputs			-10		dBc
Operating Temperature Range		-55		+85	$^{\circ}\text{C}$
Tune Input Capacitance			22		PF
Output Impedance -			50		Ω
Package Type	SK605(12.7X12.7X3.5mm)				



SMD Voltage Controlled Oscillator

Frequency 1250-1732MHz

VL1732F

[illegible]



SMD Voltage Controlled Oscillator

Frequency 1250-1732MHz

VL1732F

[illegible]



SMD Voltage Controlled Oscillator

Frequency 1250-1732MHz

VL1732F

[illegible]