

SMD Voltage Controlled Oscillator

Frequency 1550-1750MHz


VP1650M

Features

- Miniature Size
- Surface Mount Package
- Electrically Shielded
- Low Phase Noise
- Highly Linear Tuning

Description

The VP1650M is a fundamental single ended oscillator designed for use in cost sensitive wireless and telemetry applications. The device has been optimized by careful selection of the bipolar transistor and varactor diode for low phase noise and high linearity tuning characteristics.



Electrical Specifications, $T_A = +25^\circ\text{C}$, $V_{CC} = +5\text{V}$ (unless otherwise stated)

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Frequency Rangs		MHz	1550		1750
Tuning Voltage (V)		V	0.5		4.5
RF Output Power	1550-1750MHz	dBm	-2.0		2.0
Supply Voltage (VCC)		V	4.75		5.25
Supply Current (Icc)		mA		25	30
Phase Noise :					
	@10kHz Offset:	dBc/Hz		-105	-100
	@100kHz Offset:	dBc/Hz		-126	-121
Average Tuning Sensitivity	1550-1750MHz	MHz/V		56	
Harmonic Outputs		dBc		-15	
OperatingTemperature Range		$^\circ\text{C}$	-40		+85
Tune Input Capacitance		PF		20	

Comments

All specifications apply with a 50 ohm load impedance.

SMD Voltage Controlled Oscillator**Frequency****VP1650M**

Tuning Voltage (v)	Output Frequency (MHz)	Tuning Sensitivity (MHz/V)	Output Power (dBm)	Harmonic Suppression (dBc)
-55℃				
0.5	1539.0	-	-0.5	-
1.0	1572.0	-	-0.4	-
1.5	1603.0	-	-0.4	-
2.0	1632.8	-	-0.4	-
2.5	1660.2	-	-0.2	-
3.0	1691.1	-	-0.1	-
3.5	1719.7	-	-0.3	-
4.0	1746.5	-	-0.3	-
4.5	1773.1	-	-0.2	-
+25℃				
0.5	1528.0	-	-0.9	-
1.0	1561.0	-	-0.7	-
1.5	1590.8	-	-0.8	-
2.0	1620.5	-	-0.5	-
2.5	1649.9	-	-0.4	-
3.0	1679.8	-	-0.6	-
3.5	1708.1	-	-0.5	-
4.0	1736.2	-	-0.4	-
4.5	1764.1	-	-0.6	-
+85℃				
0.5	1518.0	-	-1.4	-
1.0	1551.3	-	-1.3	-
1.5	1580.6	-	-1.0	-
2.0	1611.5	-	-1.0	-
2.5	1640.6	-	-1.0	-
3.0	1669.3	-	-1.0	-
3.5	1698.7	-	-0.9	-
4.0	1727.8	-	-1.0	-
4.5	1755.1	-	-1.3	-