


SURFACE MOUNT MODEL VOLTAGE CONTROLLED OSCILLATOR

Frequency 942-962MHz


VT962M

FEATURES:

- ▶ Miniature Size
- ▶ Surface Mount Package
- ▶ Low Phase Noise Performance
- ▶ Electrically Shielded
- ▶ Highly Linear Tuning



ALL OTHER PINS ARE GROUND



Electrical Specifications, $T_A = +25^{\circ}\text{C}$, $V_{CC} = +5.0\text{V}$ (unless otherwise stated)

Parameter	Test Conditions	Min	Typ	Max	Units
Frequency Rangs		942		962	MHz
Tuning Voltage (V)		0.5		4.5	V
RF Output Power	942-962MHz	0.0		3.0	dBm
Supply Voltage (Vcc)		4.75	5	5.25	V
Supply Current (Icc)			13	15	mA
Phase Noise :					
	@10kHz Offset:		-112	-108	dBc/Hz
	@100kHz Offset:		-132	-127	dBc/Hz
Average Tuning Sensitivity	942-962MHz		12.8		MHz/V
Harmonic Outputs			-25		dBc
OperatingTemperature Range		-40		+85	$^{\circ}\text{C}$
Tune Input Capacitance			47		PF
Output Impedance -			50		Ω
Package Type	SK605(12.7X12.7X4.3mm)				



SMD Voltage Controlled Oscillator

Frequency 942-962MHz

VT962M

[illegible]