



SURFACE MOUNT MODEL VOLTAGE CONTROLLED OSCILLATOR

Frequency 900-925MHz

VT925M

FEATURES:

- ▶ Miniature Size
- ▶ Surface Mount Package
- ▶ Low Phase Noise Performance
- ▶ Electrically Shielded
- ▶ Highly Linear Tuning



Electrical Specifications, $T_A = +25^\circ\text{C}$, $V_{CC} = +5.0\text{V}$ (unless otherwise stated)

Parameter	Test Conditions	Min	Typ	Max	Units
Frequency Rangs		900		925	MHz
Tuning Voltage (V)		1.0		2.2	V
RF Output Power	900-925MHz	7.0		10.0	dBm
Supply Voltage (Vcc)		4.75		5.25	V
Supply Current (Icc)			20	23	mA
Phase Noise :					
	@10kHz Offset:		-108	-104	dBc/Hz
	@100kHz Offset:		-129	-124	dBc/Hz
Average Tuning Sensitivity	900-925MHz		40		MHz/V
Harmonic Outputs			-10		dBc
OperatingTemperature Range		-55		+85	$^\circ\text{C}$
Tune Input Capacitance			47		PF
Output Impedance -			50		Ω
Package Type	SK605(12.7X12.7X4.3mm)				



SMD Voltage Controlled Oscillator

Frequency **900-925MHz**

VT925M

[illegible]